



# ***Sampling Rules***

## ***No.124***

**RULES FOR SAMPLING,  
ANALYSIS INSTRUCTIONS  
AND CERTIFICATION**

Copyright October 2024  
Printed in England and issued by  
**GAFTA**  
**THE GRAIN AND FEED TRADE ASSOCIATION**  
**9 LINCOLN'S INN FIELDS, LONDON WC2A 3BP**  
post@gafta.com  
www.gafta.com

## **GAFTA SAMPLING RULES – CONTENTS**

1. Scope
2. Related Documents
3. Definitions
4. General
5. Equipment
6. Method of Drawing Samples
7. Preparation of Contractual Samples
8. Sample Labels
9. Making up Sets of Contractual Samples for Analysis & Arbitration
10. Appointment of Analysts by Gafta (where parties are unable to mutually agree)

**ANNEX 1: Examples of Equipment Commonly used for Sampling and Dividing (for information only)**

**ANNEX 2: Sampling Guides (for information only)**

# SAMPLING RULES

## 1. SCOPE

- 1.1. The Gafta No. 124 Sampling Rules specify the requirements for the sampling of goods traded on contracts incorporating Gafta terms and conditions. The Rules are applicable to sampling for the assessment of the quality and condition of the goods applicable to the requirements of the contract.
- 1.2. It is a requirement of Gafta contract terms and conditions that sampling is carried out by a Superintendent listed on the Gafta Approved Register of Superintendents in accordance with the Gafta 124 Sampling Rules.
- 1.3. Gafta Approved Superintendents are required to operate in accordance with the Code of Practice for the Approved Register of Superintendents.
- 1.4. The samples are dispatched to an Analyst listed on the Gafta Approved Register of Analysts who are in turn required to operate in accordance with the Code of Practice for the Approved Register of Analysts.

## 2. RELATED DOCUMENTS

- Gafta Code of Practice for the Approved Register of Superintendents
- Gafta General Code of Conduct Applicable to All Members
- Gafta Membership Rules and Membership Complaints and Disciplinary Regulations

## 3. DEFINITIONS

- 3.1. In this document the following words are used and defined as:  
**Must** – This is a requirement of the rules which has to be met.  
**Should** – This is a strong recommendation, but not mandatory.
- 3.2. **Consignment/Contractual Quantity**  
A quantity of contract goods dispatched or received at one time and covered by a specific contract or shipping document.
- 3.3. **Gafta Approved Superintendent (hereinafter “Superintendent”)**  
An organisation or company whose primary business activities are in the profession of inspection of agricultural commodities and who undertake inspections, verifications, examinations, quality and condition assessments, and sampling and measurements of goods traded in accordance with Gafta contract terms and rules. Superintendents meet the requirements of the Gafta Code of Practice for the Approved Register of Superintendents and are listed online on the Gafta website. Superintendents are appointed by (or on behalf of) Buyers and/or Sellers and must operate independently; free from any commercial, financial or other pressures.
- 3.4. **Homogenisation of sample**  
The thorough blending of individual samples by mechanical or manual means so that physical properties are evenly distributed throughout the sample. A cone shaped divider or riffle divider should be used (see also Annex 1).
- 3.5. **Lot**  
An identified quantity of material from the consignment, from which an increment sample can be taken, to determine its characteristics. Lot size can vary depending on consignment quantity size as determined by Table 1.
- 3.6. **Nominated quantity**  
The drawing of samples is based on the quantity expected to be loaded in a consignment (see Table 1). This quantity is advised in the instructions to the Superintendents. Where the instructions include a tolerance more or less, the mean quantity will be taken as the nominated quantity until and unless otherwise advised.
- 3.7. **Party/Parties**  
"Buyers" and "Sellers" are deemed to be the parties to the contract. Their respective Superintendents are appointed representatives of the “buyer” and/or “seller”.

### 3.8. Samples

#### 3.8.1. Increment Samples

Amount of sample material taken at one time by hand scoop (or whatever instrument appropriate) direct from the consignment of less than or equal to 1 kilogram in weight, or if taken mechanically, of whichever weight is appropriate to the equipment.

#### 3.8.2. Lot sample

The aggregation of all the increment samples of each lot, combined and homogenised

#### 3.8.3. Bulk Aggregate Sample

The accumulated, combined, and homogenised total of all the increment samples, or of all the lot samples (if prepared) of the contractual quantity.

#### 3.8.4. Contractual Samples

Contractual samples reduced from the bulk aggregate sample by division, sealed into not less than 3 kilogram containers each (with the exception of Rule 9.4), in as many containers as required by the Rules.

### 3.9. Sample Containers

Samples must be packed in sample containers made of appropriate material that is sufficiently strong and maintains the quality and condition of the samples with consideration given to the type of test/analysis the sample is intended for (if appropriate), for example where moisture is guaranteed under the contract then the container should maintain the moisture of the sample by being packed in a moisture proofed container.

A container is defined as a bottle, jar or tin with close fitting lid or a bag, including polythene, cotton or other suitable types of construction, which is securely tied. Such containers shall be labelled and sealed.

### 3.10. Seals/Sealed

The word "sealed" means jointly sealed samples by the Buyers and Sellers or their Superintendents and must be sealed in such a manner as to prevent any access to the sample without breaking or removing the seal. Seals must be tamper-proof and identifiable. The seal's mark should be clearly visible and identifiable.

## 4. GENERAL

- 4.1. The parties are responsible for providing their appointed Superintendents with precise instructions.
- 4.2. If one of the parties is not represented for sampling or refuses to draw and/or seal samples as called for under the contract, the other party must, under advice to that party, call upon a Superintendent from another company listed on the Approved Register of Superintendents to act on their behalf to draw and/or seal samples according to these Rules. Extra expenses incurred in this connection must be borne by the defaulting party.  
**NOTE: Not applicable when contract states 'Quality (Certificate) Final' at loading or at discharge.**
- 4.3. Where the contract provides that a certificate(s) of a government or authority at the port of loading shall be final as to quality, then the government or authority shall be solely responsible for drawing samples and Rules 4.2, and 9.1.5 do not apply.
- 4.4. The sampling procedures must be carried out in such a way that the sampled material is protected from any source of accidental contamination caused by rain, dust, etc.
- 4.5. All the sampling procedures must be carried out over a sufficiently short period of time to avoid any modification of the volatile substances in the samples. If one of the sampling stages takes a long time, the increments, individually or combined, must be kept in sealed and secured containers.
- 4.6. Precautions must be taken to guarantee the integrity of all samples from the moment they are taken to the moment they are used in the laboratory.
- 4.7. The location selected for sampling must be at the point of loading into or discharge from the ship, barge, wagon or lorry or at the time of entry into or exit from the silo or warehouse, as agreed between the Superintendents and/or parties concerned.
- 4.8. If the facility is unsafe, or operations preclude access to the hold or a mutually agreed acceptable sampling point, the Superintendents should stop the operation in order to draw increment samples as required by these Rules. The parties are deemed to have agreed to this procedure.
- 4.9. The methods of taking samples from flowing lots must be adapted to the speed at which the products are flowing.

## 5. EQUIPMENT

- 5.1. All sampling equipment must be clean, dry, free from foreign odours and made from material which will not contaminate or alter the quality and the condition of the goods being sampled.
- 5.2. Sampling equipment must be thoroughly cleaned between consignments. Dividing equipment must be thoroughly cleaned between each sample to avoid cross-contamination.
- 5.3. The most suitable equipment should be chosen taking into account the product to be sampled, the quantity required and the containers to be used.
- 5.4. Mechanical sampling devices must have suitable points of access for the examination, cleaning, maintenance, and repair of all surfaces subject to wear.
- 5.5. Any nearby equipment must not adversely affect the operation of the sampler or delay its operation in any manner.
- 5.6. Lighting in the area of the sampler must be sufficiently intense and preferably permanently installed in order to allow the visual inspections of the sampling system.
- 5.7. The division, classification and sealing of contractual samples must always be carried out in daylight or, in artificial light if considered adequate and mutually agreed by the Superintendents.
- 5.8. Whenever possible, sampling should be carried out when the products are flowing so that all the constituent parts of the lot have the same probability of being sampled.

*Examples of the types of equipment used for sampling and dividing are given in Annex 1*

## 6. METHOD OF DRAWING SAMPLES

### 6.1. Sampling Points

- 6.1.1. Sampling points must be carefully selected, and agreed by the Superintendents, at a point where the increment samples drawn are representative of the goods loaded and/or discharged and/or transhipped.

### 6.2. Drawing Increment Samples

- 6.2.1. According to the rate of loading or discharge, increment samples must be taken throughout, uniformly and systematically, in order to achieve representative samples of the contractual quantity.
- 6.2.2. Increment samples must be taken from a moving stream unless this is not possible (see 6.3 Specific Requirements below).
- 6.2.3. Increment samples must be taken from the nearest practical point to the vessel/hold during loading or discharge.
- 6.2.4. Increment samples must be taken by hand scoop, spear, or by other mutually agreed equipment throughout loading or discharge.
- 6.2.5. As many increment samples as practically and physically possible (but not less than as set out in Table 1 below) must be taken throughout discharge/loading, and where possible, each increment sample should not exceed 1 kilogram.
- 6.2.6. All increment samples must be placed in mutually agreed suitable container(s), to be kept closed and secure.
- 6.2.7. When full and/or at the end of each work period and/or if the containers need to be moved, these containers must be sealed and placed in a mutually agreed secure place for safe custody until required for reduction and division.
- 6.2.8. All increment samples must be taken from the total contractual quantity before moving to the next stage of the process (division and reduction). The exceptions to this are when pre-reduction is mutually agreed (see section 7.5) or when the standing-in clause applies (see section 9.5.4).

### 6.3. Specific Requirements

- 6.3.1. **Loading/discharge by grab:** Increment samples must be drawn from the quay or vessel's hold from the bulk, excluding the run.
- 6.3.2. **Shipping Containers:** Increment samples must be taken from the moving stream during stuffing. For shipping containers loaded with bags, see 'Goods in Bags'.
- 6.3.3. **Goods in Bags:** A sample plan must be created to take samples from random bags as follows:
  - <100 bags – samples taken from a minimum of 20 bags
  - 100-10,000 bags – samples taken from a minimum of 50 bags
  - 10,000+ bags – samples taken from 0.5% of the bags i.e., 1 in 200 bags,

Samples from each bag are taken by spearing each bag 3 times in the top, middle and bottom of the bag.

Where it is not possible to spear efficiently, the bag must be opened, and a hand scoop used.

6.3.4. **Goods in Bags for Cutting & Starting (Bleeding):** Where goods are loaded from bags cut and bled into the hold, samples must be taken from the nearest point to the hold, either from the moving stream or by spearing the bags before bleeding, as per 'Goods in Bags' above.

6.3.5. **Road/Rail Wagons & Vehicles:** A sample plan must be created to take samples by spear as follows:

- Wagons/Vehicles weighing up to 15 tonnes – minimum 5 sample/spear points
- Wagons/Vehicles weighing 16-30 tonnes – minimum 8 sample/spear points
- Wagons/Vehicles weighing 30+ tonnes – minimum 11 sample/spear points

Alternatively, samples can be taken from the moving stream during loading and discharge by hand scoop or other suitable equipment, at the closest practical point to the wagon/vehicle (e.g., outlet of the filling hopper during loading, or outlet of the wagon/vehicle during discharge).

6.3.6. **Molasses:** Every hour throughout loading half-litre samples shall be drawn from the sample points in all the loading pipelines.

**Table 1: Increment sampling - size of lots, number and size of consignments**

Nominated Quantity	Tonnes	0-5,000	5,001-10,000	10,001 - 25,000	>25,000
Lot size	Tonnes	500	1,000	2,500	5,000
No. of increments per lot	Number	min 20	min 30	min 40	min 50
Min bulk (aggregate) sample per lot	Kilos	20	30	40	50
Max weight of increments	Kilos	1	1	1	1

**Note:** A separate Sampling Guide is available from Gafta which illustrates how Table 1 should be applied. Sampling Guides are intended for guidance/illustrative purposes only and are not considered to form part of the contract. See Annex 2.

## 7. PREPARATION OF THE CONTRACTUAL SAMPLES

- 7.1. The increment samples representing the total contractual quantity must be homogenised in a location free from any possible contamination to produce the bulk aggregate sample.
- 7.2. The bulk aggregate sample is then divided and reduced to the required number of contractual samples.
- 7.3. Reduction of the bulk aggregate sample must be carried out using an appropriate Boerner type or riffle divider or any other method mutually agreed by the Superintendents.
- 7.4. Contractual samples must be placed in suitable containers and sealed without delay.

### 7.5. Pre-Reduction of Lot Sample

- 7.5.1. This procedure is allowed when physical and/or practical restrictions prevent the homogenisation of all the increment samples representing the contractual quantity to produce the bulk aggregate sample, by mutual agreement of the Superintendents.
- 7.5.2. For this procedure, increment samples representing each lot are taken and combined to produce a lot sample (see Table 1 above).
- 7.5.3. Parties may agree to jointly seal these lot samples.
- 7.5.4. After homogenisation each lot sample is then reduced to not less than 25% of the original quantity of the lot sample.
- 7.5.5. Reduction of the lot samples must be carried out using an appropriate Boerner type or riffle divider or any other method mutually agreed by the Superintendents.
- 7.5.6. The reduced lot samples are then combined and homogenised to create a pre-reduced bulk aggregate sample.
- 7.5.7. Preparation of the Contractual Sample is then followed from point 7.2 above.

**Note:** A separate Sampling Guide is available from Gafta which illustrates how pre-reduction should be applied. Sampling Guides are intended for guidance/illustrative purposes only and are not considered to form part of the contract. See Annex 2.

#### 7.6. Preparation of contractual/analysis samples for Molasses

7.6.1. A bulk aggregate sample of all the half-litre samples taken must be homogenized and then split into 6 contractual samples of approx. 1 litre each, jointly sealed and numbered 1-6.

### 8. SAMPLE LABELS

8.1. Every contractual sample shall be sealed and shall bear the name of the ship, the quantity represented by the sample and the date the sample was sealed. Other pertinent information may be required on the label as follows:

Sender .....  
Transport / M.V.....  
From .....  
To.....  
Commodity.....  
Bags/Bulk.....  
Marks .....  
Shipper/Sellers/Buyers .....  
Set No ..... Sample No. ....  
Date and Place of Sealing .....  
Quantity represented by this sample.....  
Part Total Quantity of .....

\*Arbitration (Quality/Rye Terms), Natural Weight/Analysis .....

\* delete as appropriate

D/O	Receiver	Quantity
B/L		
No.		
Seals .....		

### 9. MAKING UP SETS OF CONTRACTUAL SAMPLES FOR ANALYSIS & ARBITRATION

#### 9.1. General

9.1.1. A 'set' of contractual samples consists of the number of samples determined by commodity as per point 9.5 below.

9.1.2. Per 5,000 tonnes of the contractual quantity, or part thereof, one set of contractual samples must be prepared, except where such a balance does not exceed 250 tonnes. Each sample must be not less than 3 kilograms.

**NOTE: where certificates are issued by a government or authority, arbitration samples may not be obtainable.**

9.1.3. In accordance with the contractual terms, analysis samples must be dispatched to an analyst on the Gafta Approved Register of Analysts within 14 consecutive days of sealing. The choice of analyst is that of the instructing party or their representative unless otherwise agreed. Instructions specifying what analyses are to be carried out, along with another pertinent instructions, must accompany the samples.

9.1.4. Upon receipt of the certificate of analysis from the analyst, a copy must be sent to the other party within 14 consecutive days.

9.1.5. The Superintendent must state on the certificate the name of the analyst(s) who carried out the analysis and the method(s) used.

9.1.6. Unless specifically instructed by the parties, the Superintendent is not required to report analytical uncertainty on the certificate of analysis.

- 9.1.7. Failure to complete points 9.1.3 and 9.1.4 above within the specified timescales will deem any claim for rejection or allowances waived and absolutely barred, unless the arbitrators or Board of Appeal determine otherwise.
- 9.1.8. Arbitration samples drawn for goods traded on contracts stating 'Quality (Certificate) Final' at loading or at discharge cannot be used to challenge the quality specifications which are included in the 'Quality (Certificate) Final' certificate, unless otherwise determined by arbitrators or Board of Appeal.

## **9.2. Reduction of contractual samples prior to dispatch to analysts for contractual analysis**

- 9.2.1. These Rules allow for the homogenisation and reduction of all the contractual samples prior to dispatch for contractual analysis.
- 9.2.2. The reduction of contractual samples must be carried out by another analyst on The Gafta Approved Register of Analysts.
- 9.2.3. The resulting sealed sample of not less than 3 kilograms representing the total contractual quantity must be forwarded to contractually nominated analyst on the Approved Register of Analysts for analysis in accordance with the contract and the provisions of these Rules.

*NOTE: A separate Sampling Guide is available from Gafta which illustrates how reduction of contractual samples should be applied. Sampling Guides are intended for guidance/illustrative purposes only and are not considered to form part of the contract. See Annex 2.*

## **9.3. Retention of Samples**

- 9.3.1. Any samples not required for analysis or arbitration must be retained by the Superintendent for a period of 3 months from the date of sealing, unless otherwise instructed in writing by either party to the contract. At the expiry of 3 months from the date of sealing, the Superintendent must dispose of the samples.
- 9.3.2. All contractual samples drawn and sealed under these rules by Buyers and/or Sellers, or their respective representatives will remain the property of both parties to the contract.
- 9.3.3. Whilst Superintendents must make every effort to protect all samples entrusted to its care, neither the Superintendents nor any of its servants or agents shall be under any liability whatsoever to any party having any interest in any samples received by it in pursuance of these Rules for any loss or damage to any such sample.

## **9.4. Mycotoxin and Genetically Modified Organisms (GMO) Samples**

- 9.4.1. Specific instructions will be provided to the Superintendent to make up one additional sample divided from the aggregate bulk sample when:
- 9.4.2. The contract includes maximum levels for mycotoxins,
- 9.4.3. The contract includes a warranty or guarantee relating to GMO.
- 9.4.4. In the case of maize (corn) the size of the sample must be at least 10 kilograms.

## **9.5. Commodity and/or contract specific requirements**

### **9.5.1. Grains, Pulses, Seeds & Rice (excluding Malting Barley, including feed grains and feed pulses)**

- 9.5.1.1. One set of samples consists of the following:
- Sample 1: for analysis
  - Sample 2: for arbitration
  - Sample 3: spare
- 9.5.1.2. Samples are held by the Sellers (or their representative).
- 9.5.1.3. **Note:** Parties can request the Superintendent to draw additional analysis samples where the contract specifies additional quality analyses are required.
- 9.5.1.4. The analysis samples must be dispatched to one of the analysts listed on the Gafta Approved Register of Analysts within 14 consecutive days of sealing. In the event that this option is not decided at the time of the contract, the choice of analyst is that of the instructing party.

### **9.5.2. Malting Barley**

- 9.5.2.1. Two duplicate sets of samples are required, to be marked "Set 1" and "Set 2" respectively, and each set consists of the following:
- Sample 1: for analysis
  - Sample 2: for analysis



Sample 3: for analysis

Sample 4: for arbitration

9.5.2.2. Unless otherwise agreed by the Superintendents:

“Set 1” samples to be held by the Buyers (or their representative).

“Set 2” samples to be held by the Sellers (or their representative).

9.5.2.3. Analysis samples with instructions shall be sent to an analyst listed on the Approved Register of Analysts by the last buyers within 21 consecutive days of sealing.

9.5.2.4. Either party has the right to request a second analysis. Within 7 consecutive days from receipt of the first certificate notification of such claim must be served to the other party and further analysis samples with instructions shall be sent to an analyst listed on the Approved Register of Analysts.

**9.5.3. Feedingstuffs & Biomass and Marine & Animal Products (excluding feed grains and feed pulses)**

9.5.3.1. One set of samples is required consisting of the following:

Sample 1: for analysis

Sample 2: for analysis

Sample 3: for analysis

Sample 4: for arbitration

9.5.3.2. Unless otherwise agreed by the Superintendents:

Two samples from each set are held by the Buyers (or their representative)

Two samples from each set are held by the Sellers (or their representative)

9.5.3.3. Where moisture is guaranteed, one set of samples must be drawn and the result of the first analysis test shall be final.

9.5.3.4. **Second & Third Analyses - Applicable to feedingstuffs, biomass and marine & animal products (excluding feed grains and feed pulses)**

Where contractual allowances apply second and third analysis tests are permitted as follows:

**Second Analysis:** Within 14 consecutive days of receipt copy of the certificate of analysis either party can give notice to the other party that they require a second analysis, and to dispatch another of the sealed samples and analysis instructions, without delay to another analyst listed on the Approved Register of Analysts. The mean of the two analyses shall be accepted as final if the variation does not exceed 0.50%.

**Third Analysis:** If the variation between first and second analysis does exceed 0.50% then either party have the right to request a third analysis. Notification must be made to the other party with within 14 consecutive days of receipt (by them) of the true copy of the certificate of the second analysis, and a third sealed sample must be dispatched without delay to a third laboratory on the Gafta Approved Register of Analysts, mutually agreed between both parties. The mean of the two results closest to each other of all three analyses must be accepted as final and binding, except where the difference between the three results is the same, in which case the average of three tests shall apply.

**9.5.4 Feedingstuffs sold on a contract including the standing-in clause (Gafta 131)**

9.5.4.1 If the goods concerned in the contract are sold under a standing-in clause and form part of a larger quantity in a hold, Buyers are deemed to have agreed, for their proportion, to abide by the samples drawn and sealed from that hold, for the purposes of analysis and/or arbitration.

9.5.4.2 Goods from each hold shall be sampled and samples analysed separately in accordance with these Rules.

9.5.4.3 If the goods are discharged simultaneously from more than one hold, but not more than two holds, through one discharging unit only, the standing-in quantity shall be the total tonnage of those holds for any receiver taking delivery from them.

9.5.4.4 Samples must be drawn and sealed conjointly by the first CIF seller(s) and the CIF receiver(s) or their respective agents.

9.5.4.5 The first CIF seller(s) or their agents are responsible for forwarding samples and analytical instructions to two from Gafta Approved Register of Analysts, the choice of which to be mutually agreed between first CIF seller(s) and the CIF receiver(s). A certificate of analysis is to be obtained from each analyst.

9.5.4.6 When sending instructions to the analysts the instructing party shall advise the analysts of the following:

- the bill of lading number
- the delivery order number
- the name of the vessel and the date of sealing
- the hold number

- the names of all receivers who have agreed to stand-in, together with their individual tonnages
- 9.5.4.7 Sellers must forward copies of the certificates of analysis showing the relevant details of the receiver's proportion to each CIF receiver who has contractually requested an analysis.
- 9.5.4.8 Copies of the certificate of analyses must be sent no later than 14 consecutive days from receipt of the last certificate by the Buyers to the Sellers.
- 9.5.4.9 The mean of the two tests shall apply for the purpose of allowances or arbitration and must be accepted as final if the variation does not exceed 0.50%.
- 9.5.4.10 If the variation stated exceeds 0.50% then, the first CIF seller can request, within 14 consecutive days of receipt of the last certificate of analysis, a third test carried out by a mutually agreed third laboratory from the Gafta Approved Register of Analysts. In case the first CIF seller does not use this option, within 7 consecutive days the CIF receiver(s) have the option to ask for the third test. The mean of the two analyses of all three tests nearest to each other must be accepted as final and binding on both parties, except where the difference between the three results is the same, in which case the average of three tests will apply.
- 9.5.4.11 The average of the first and second moisture test results shall be used as the calculating factor for the third test.
- 9.5.5. Fertiliser (sold on Gafta Contract No. 114)**
- 9.5.5.1. One set of samples consists of the following:
- Sample 1: for analysis
  - Sample 2: for analysis
  - Sample 3: arbitration/analysis
- 9.5.5.2. Unless otherwise agreed by the Superintendents:
- 2 samples from each of the sets to be held by the Buyers (or their representative).
  - 1 sample from each of the sets to be retained by Sellers (or their representative).
- 9.5.5.3. For parcels smaller than 1,500 tonnes, samples must be sealed per 250 tonnes.
- 9.5.5.4. Buyers arrange analysis with an independent laboratory of their choice within 14 consecutive days of completion of discharge.
- 9.5.5.5. Where no allowance is payable, costs of analysis are for the Buyers' account.
- 9.5.5.6. Sellers reserve the right to request a second analysis within 14 consecutive days of receipt of the certificate of analysis of the first analysis. Allowances are then based on the results of the second analysis.
- 9.5.5.7. Where no allowance is payable after the second analysis, the cost of the second analysis is for the sellers' account.
- 9.5.6. Molasses (sold on Gafta Contract No. 115)**
- 9.5.6.1. One set consists of 6 samples of approximately 1 litre each, jointly sealed and numbered (see Rule 7.6).
- 9.5.6.2. Unless otherwise agreed by the Superintendents:
- Samples numbered 1, 2, 5 and 6 to be held by the Buyers (or their representative)
  - Samples numbered 3 and 4 to be held by the Sellers (or their representative).
- 9.5.6.3. Buyers and Sellers must each send one contractual sample to an independent laboratory of their choice within 14 consecutive days of sealing.
- 9.5.6.4. Jointly sealed samples may also be taken from the tanks of Buyers' vessel for verification purposes.
- 9.5.7. For Ex-store Contracts Nos. 109 and 110**
- 9.5.7.1. One set of contractual samples is required for analysis for the purposes of the contractual warranties.
- 9.5.7.2. The party landing the goods must appoint and instruct a Superintendent from the Approved Register of Superintendents to draw and seal fully representative samples.
- 9.5.7.3. Such samples will be drawn during the discharge of the importing vessel at the port in the country of the delivery place named in the contract.
- 9.5.7.4. Notwithstanding the provisions of Definition 3.10, every sample must be sealed and labelled with:
- The name of the ship
  - The contractual quantity represented by the sample
  - The total quantity of which each sample forms part
  - The date the sample was sealed
  - A statement that the samples were sealed and taken in accordance with these Rules for analysis pursuant to Contracts No. 109 or No. 110

- Any other pertinent information which may be required
- 9.5.7.5. The laboratory must be instructed to record this information on the analysis certificate.
- 9.5.7.6. If samples are drawn at discharge of the vessel, ex-store Sellers have the option of using the same analysis certificates for the ex-store contract(s) relating to goods discharged from that vessel.
- 9.5.8. For Goods Damaged and/or Out of Condition - "rye terms"**
- 9.5.8.1. For contracts on "rye terms", without prejudice to Sellers' rights and responsibilities under the contract, Sellers' Superintendents at Buyers' request must jointly seal samples of goods arriving damaged or out of condition in accordance with the provisions of this Rule.
- 9.5.8.2. For "rye terms" contracts samples must be drawn by the Superintendents in accordance with the provisions of these Rules.
- 9.5.8.3. Goods arriving damaged and/or out of condition, including "rye terms", must be sampled on board the vessel at time of discharge, but in cases where both parties agree that it is not practicable for the classification and sampling to be carried out on board, then goods damaged and/or out of condition should be landed on the quay or discharged to lighter for the purpose of such classification.  
Sampling and sealing of classified sets of samples must take place within the port area as soon as possible after the damaged goods are landed or discharged into lighter, always provided that all the damaged and/or out of condition and sound goods are classified.  
In the event of agreement not being reached, without prejudice to the parties' rights and responsibilities under the contract, either party or both parties must, after giving notice to the other party, appoint a Superintendent from another company listed on the Approved Register of Superintendents to act on behalf of the other party and samples must be drawn jointly under all reserves.
- 9.5.8.4. The sets of sealed samples in classified lots must be a fair and true indication of the degree of damage and/or out of condition goods, and the sample labels must show the proportion of the tonnage so affected. Lumpy goods, if in bags, must be sampled by cutting from top to bottom and withdrawing samples by hand if necessary. Water, or oil, or liquid and/or chemical damaged goods must be sealed in plastic bags.
- 9.5.8.5. The sample labels must show the gross discharged weight of each classification it represents inclusive of any extraneous substance.
- 9.5.8.6. Sets of samples drawn and sealed pursuant to point 6.3 and Section 9 must be taken for each classification as follows:
- i. lumpy/damaged/out of condition - For Buyers
  - ii. lumpy/damaged/out of condition - For Sellers
  - iii. water, or oil, or liquid and/or chemical damaged goods - For Buyers
  - iv. water, or oil, or liquid and/or chemical damaged goods - For Sellers
  - v. sound goods for comparison purposes of 1 kilo irrespective of tonnage - For Buyers
  - vi. sound goods for comparison purposes of 1 kilo irrespective of tonnage - For Sellers
- 9.5.8.7. The "rye terms" samples (held by the Sellers and held by the Buyers) must be forwarded to Gafta within 7 consecutive days of discharge from the vessel or on completion of classification and sealing, whichever happens later. The expenses incurred in sealing and forwarding of samples must be paid half by Buyers and half by Sellers.
- 9.5.8.8. In the event of it being proven to the satisfaction of the arbitrators that one set of sealed samples, in part or whole, has been lost, damaged or destroyed prior to the expiration of the period for forwarding permitted under this clause, or that the said set having been forwarded in accordance with this clause has been lost, damaged or destroyed during transit, then either party is entitled to proceed to arbitration on the other complete set of sealed samples.

## **10. APPOINTMENT OF ANALYSTS BY GAFTA (where parties are unable to mutually agree)**

- 10.1 Where parties are unable to mutually agree the choice of Analyst(s) under clauses 9.5.3.4 or 9.5.4.5, an application must be made to Gafta to appoint from the Gafta Approved Register.
- 10.2 Applications to Gafta for the appointment of an analyst(s) shall be accompanied by:-
- (a) prima facie evidence that the parties have entered into a contract subject to the Gafta No.124 Sampling Rules,
  - (b) the clause of the Gafta No.124 for which the application for appointment of an analyst(s) is made [i.e. 3<sup>rd</sup> analysis (9.5.3.4) or standing in provisions (9.5.4.5)]
  - (c) in the case of 9.5.4.5 whether one or both analysts to be appointed by Gafta
  - (d) appointment fee of GBP 150.00 from both parties (payment via invoice issued by Gafta upon receipt of application)
  - (e) the location where the samples are being taken
  - (f) the name of the superintendent organisation(s) appointed to represent the party(ies)

- (g) copy of the notice to the other party informing them that as they have failed to mutually agree an Analyst(s) that you are applying to the Association for an appointment to be made

## **Annex 1**

### **Examples of Equipment Commonly used for Sampling and Dividing**

Examples for information only.

NOTE This list is not exhaustive.

#### **A.1. Examples of mechanical sampling devices used on flowing grain, oilseeds and processed products**

##### **A.1.1. Crosscut sampling devices**

Crosscut sampling devices allow a complete cross-section of a freely falling flow of grains to be taken. They may be open-nozzle sampling devices, tubular sampling devices with adjustable apertures or tubular sampling devices with a worm screw.

##### **A.1.2. Full-flow diverter-type sampling devices**

In this type of sampling device, a flap or shutter intermittently diverts the flow of grain.

##### **A.1.3. Rotating cup sampling devices**

The freely falling flow of grain is intermittently sampled by a cup which rotates around a central vertical axis.

##### **A.1.4. Bucket elevator sampling devices**

This type of sampling device samples grain from a moving belt or conveyor. Buckets travelling in a continuous loop take samples over the entire width of the grain flow because the configuration of the lateral rollers concentrates the grain on the belt. Once the buckets have pivoted around the upper roller, the samples are delivered into the hopper.

#### **A.2. Examples of manual sampling devices used on flowing grain, oilseeds and processed products**

##### **A.2.1. Hand scoop**

The hand scoop is a sampling device consisting of a rigid material scoop attached to handle.

##### **A.2.2. The Pelican sampler**

A Pelican sampler is a cowhide pouch attached to a metal frame at the end of a hardwood or tubular metal handle. It is used to obtain samples from freefalling grain, e.g. from a spout discharge to the hold of a ship.

**Note:** If the spout is sloping, the grain stream is likely to be stratified. It is important, therefore, that the sampler is cut through the stream from one side to the other in a single motion to obtain a good sample.

##### **A.2.3. The Ellis Cup sampler**

This is a hand-held scoop designed for obtaining small samples from bulk grain on moving conveyor belts. The cup should obtain a vertical section of the flowing grain at the point where it is inserted into the stream.

#### **A.3. Examples of manual sampling devices used on static grains, oilseeds and processed products**

##### **A.3.1. Probes or spears**

Probes are hollow shafts with single or multiple apertures (holes) along their length; some have compartments inside. They are pointed at one end and driven into the product to be sampled (through bag or tote material if applicable) and when removed a sample of the product is contained inside. Probes are of differing size and length – the correct size and length must be selected to suit the product being sampled and the size of the bag/tote/compartments inside which the product is held. The probe must not select the product by size or damage the product being sampled.

Manual probe sampling is typically not suitable for products in compartments of more than 2 metres depth.

#### **A.4. Examples of mechanical sampling devices used on static grains, oilseeds and processed products**

##### **A.4.1. Pneumatic, suction or vacuum sampling device**

Pneumatic probe sampling systems use a sampling probe (compartmentalized or core) that is inserted into a bulk lot of grain. When the probe reaches the maximum depth of a conveyance, a pneumatic recovery system transports the sample from the probe and delivers the sample, through a series of delivery lines, to a sample collection unit.

In general, pneumatic sampling devices are not suitable for milled products.

##### **A.4.2. Archimedes' screw sampling probe**

A small, portable, electric sampling probe. The Archimedes screw inside the probe/cylinder, driven by a small motor, draws the sample out of the product which is captured at the top of the probe.

#### **A.5. Examples of Instruments used to homogenise and divide samples**

##### **A.5.1. Cone shaped dividers (Boerner type)**

The sample is poured into a cone shaped hopper which separates the sample into two separate collection boxes. One collection box is returned to the hopper, the other is discarded. This is repeated as many times as required to achieve the sample of the required size.

Can be static, or mechanical. The hopper rotates with the mechanical divider.

##### **A.5.2. Multiple-slot dividers (with partitions and plates)**

Also known as a Riffle Divider.

The sample is poured into a hopper and passes between a number of plates or partitions to divide the sample into two separate collection boxes. One collection box is returned to the hopper, the other is discarded. This is repeated as many times as required to achieve the sample of the required size.

The correct size and type of multiple slot divider must be selected for the product being divided.

Care should be taken to ensure the riffle divider is used correctly, as the accuracy of this equipment is heavily influenced by operator error. It is important that the mass of the seed be uniformly distributed along the entire width of the divider before being poured onto the rifles.

##### **Homogenisation using a cone shaped divider or riffle divider**

1. Pour sample into the hopper
2. Two sub samples are obtained in the collection boxes
3. Repeat steps 1 and 2 above at least three times returning both sub samples into the hopper together.

## **Annex 2**

### **Sampling Guides**

**For illustration purposes only - this guidance should be read in conjunction with the Sampling Rules Gafta No.124**

These documents can be accessed on the Gafta website: [www.gafta.com](http://www.gafta.com) [link]

#### **Drawing and Sealing Samples - Standard Method:**

[Sampling Guide - Standard Method](#) [link]

#### **Drawing and Sealing Samples – pre-reduction of bulk lot samples:**

[Sampling Guide - Pre-Reduction of bulk lot samples](#) [link]

#### **Drawing and Sealing Samples - with reduction of contractual samples for dispatch to analysts:**

[Sampling Guide - Reduction of contractual samples for dispatch to analysts](#) [link]

**Effective for contracts dated from 01/10/2024**

Copyright October 2024

Printed in England and issued by

**GAFTA**

**THE GRAIN AND FEED TRADE ASSOCIATION  
9 LINCOLN'S INN FIELDS, LONDON WC2A 3BP**

[post@gafta.com](mailto:post@gafta.com)

[www.gafta.com](http://www.gafta.com)